

## JLG 150HAX



- Largest self-propelled lift in the world at a working height of 47 m
- Longest outreach at 24.16 m of any self-propelled lift in the world
- Up and over height 24.38 m
- Fast boom and drive speeds improve work productivity
- Four wheel drive and four wheel steer is standard
- Proportional controls achieve smoother movement for operator comfort
- Excellent manoeuvrability for positioning of machine and platform

For more details check the JLG Technical Specification Guide or ask your local JLG representative.



### Proportional Drive Controls

Proportional controls provide operation for telescoping the main and tower boom and drive, lift and swing.



### 165° Powered Rotator

A sealed hydraulic platform rotator with 165 degrees of motion for improved positioning.



### Moveable Ground Control

The ground controls can be detached from the machine housing to aid the operator when loading the machine for transport.



### Ground to Platform Intercom System

An intercom system is supplied to permit communication between platform and ground personnel.



### Plate Steel Boom

Provides longer service life and minimal deflection for operator comfort.



### Extending Axles

Help to reduce stowed width for travel in confined areas and for ease of transport.

### JLGEUROPE

JLG Industries (Europe), A Division of JLG Industries, Inc.  
Kilmartin Place, Tannochside Park,  
Uddingston, G71 5PH, Scotland.  
Tel: 01698 811005  
Fax: 01698 811055

[www.jlg.com](http://www.jlg.com)



# 150 HAX ARTICULATING BOOM LIFT

**150HAX**

Platform Height	45.72 m
Horizontal Outreach	24.16 m
Up and Over Height	24.38 m
Swing (Continuous)	360°
Platform Capacity – Unrestricted	230 kg
Platform Rotator (Hydraulic)	165°
A. Platform Size	0.91 m x 2.44 m
B. Overall Width (Axles Retracted)	3.51 m
C. Overall Width (Axles Extended)	5.49 m
D. Tailswing (working condition)	Zero
E. Stowed Height	4.27 m
F. Stowed Length	12.01 m
G. Wheelbase	5.49 m
H. Ground Clearance	0.30 m
Gross Vehicle Weight*	25,855 kg
Maximum Ground Bearing Pressure	7.9 kg/cm <sup>2</sup>
Maximum Tyre Load	12,000 kg
Drive Speed	4.3 km/h
Gradeability	31%
Tyres	445/65R22.5 Foam Filled
Turning Radius (Inside) - Axles Retracted	4.52 m
Turning Radius (Inside) - Axles Extended	4.45 m
Turning Radius (Outside) - Axles Retracted	8.23 m
Turning Radius (Outside) - Axles Extended	9.17 m
Diesel Engine – Cummins 4B3-9C	58 kW
Fuel Tank Capacity	257.4 L
Hydraulic Reservoir	469.3 L
Auxiliary Power	12V DC

\*Certain options or country standards will increase weight.

Specifications may change to meet country standards or with the addition of optional equipment.

